

(12) UK Patent Application (19) GB (11) 2 353 328 (13) A

(43) Date of A Publication 21.02.2001

(21) Application No 0020230.9

(22) Date of Filing 16.08.2000

(30) Priority Data

(31) 09378647 (32) 20.08.1999 (33) US

(71) Applicant(s)

Cummins Engine Company, Inc.
(Incorporated in USA - Indiana)
500 Jackson Street, Columbus, Indiana 47201,
United States of America

(72) Inventor(s)

Thomas L McKinley
Philip M Dimpelfeld
John M Mulloy

(51) INT CL⁷

F02M 25/07, F02D 9/04 9/06 21/08

(52) UK CL (Edition S)

F1B BBA BB140 BB220 BB228 BB236 BB300

(56) Documents Cited

EP 0869275 A1 EP 0622533 A1 JP 110082070 A
US 5771867 A

(58) Field of Search

UK CL (Edition R) F1B BB140
INT CL⁷ F02D 9/04 21/08, F02M 25/07
online: EPODOC, JAPIO, WPI, TXTEP, TXTGB, TXTUS,
TXTWO, MOBILITY


(74) Agent and/or Address for Service

fJ Cleveland
40-43 Chancery Lane, LONDON, WC2A 1JQ,
United Kingdom

(54) Abstract Title

Turbocharged i.c. engine with EGR system and exhaust throttle

(57) An exhaust gas recirculation EGR enhancement system 12 for a turbocharged i.e. engine 10 includes a throttle valve 54 arranged in the exhaust duct 22 of the engine, downstream of the EGR system 12. The throttle valve 54 is controlled in response to engine load and engine speed to selectively provide back pressure upstream of the throttle valve 54 to selectively drive an EGR exhaust flow through an EGR duct 40 to the intake manifold 18. An embodiment of the EGR system includes a cooler 46 that lowers the temperature of the EGR exhaust flow to provide better reductions in nitric oxide emissions. The exhaust turbine 28 of the turbocharger 26 may be of variable geometry type 28 or of the fixed geometry type (28', fig.2) to provide a turbine with a fixed or variable swallowing capacity. The fixed geometry turbine (28', fig.2) is preferably equipped to allow excess pressure to be released through a wastegate duct 66 arranged in fluid parallel with the exhaust turbine (28') thereby allowing for higher power and higher speeds. The EGR system may be controlled to provide compression braking.



GB 2 353 328 A




Fig. 1




Fig. 2




Fig. 3

**AN EXHAUST GAS RECIRCULATION SYSTEM
FOR AND A METHOD OF OPERATING A
TURBOCHARGED INTERNAL COMBUSTION ENGINE**

5 The present invention generally relates to turbocharged internal combustion engines and more particularly relates to exhaust gas recirculation systems for turbocharged internal combustion engines.

10 In internal combustion engines, a process known as exhaust gas recirculation (EGR) is used to reduce the amount of nitric oxide (NO_x) emissions. In general, EGR involves routing a portion of the exhaust gas back into the intake air flow. In an engine where exhaust back pressure is greater than intake air pressure (e.g., most normally aspirated engines) an EGR flow can be realized simply by connecting a conduit between the exhaust and intake ducts. The
15 flow from the exhaust manifold is drawn to the lower pressure of the intake because of the negative pressure differential. However, in a turbocharged internal combustion engine having a charged intake, an unfavorable pressure differential must be overcome.

20 More particularly, in turbocharged diesel engines, the recirculated exhaust gas flow is typically introduced into the intake air downstream of the

turbocompressor and intercooler components in order to avoid degradation of these components. Unfortunately, the intake air is pressurized at this location, presenting an unfavorable intake to exhaust pressure ratio for transporting EGR gases. Diesel engines with efficient, well-matched turbochargers have an

5 insufficient exhaust-to-intake pressure differential during some operating states to induce an amount of EGR flow sufficient to reduce nitric oxide emissions in compliance with environmental emissions regulations. For example, when an engine is running at a low speed under a high load, the exhaust temperature can be hot enough that the intake manifold pressure is higher than the exhaust

10 manifold pressure. If a connection is opened between the intake manifold and the exhaust manifold through the EGR system, air flows from the intake manifold into the exhaust manifold, rather than the desired flow from the exhaust manifold to the intake manifold.

15 Various EGR systems are known which attempt to overcome this unfavorable pressure differential via a supplemental pump or compressor operable to force flow through the EGR duct from the exhaust manifold to the intake manifold. Such EGR compressors can be mechanically driven, electric, or exhaust-driven by a second turbocompressor. It is also known to provide a supplemental

20 compressor in the EGR system to drive flow. However, they require a relatively large amount of energy which tends to substantially sacrifice fuel

economy. These systems also increase the complexity and cost of assembling an engine.

Systems are also known which attempt to achieve exhaust-to-intake EGR flow
5 by increasing the pressure in the exhaust manifold (backpressure). This can be achieved with careful engine design choices, such as the selection of a turbocharger having a particular fixed-geometry turbine size to yield an appropriate pressure differential. To increase EGR flow in a particular engine, a fixed-geometry turbocharger could be selected to have a relatively small size,
10 having a correspondingly small swallowing capacity and a high flow restriction. The high flow restriction would provide increased backpressure upstream of the turbine sufficient to drive the EGR flow back to the intake manifold. Unfortunately, a turbocharger turbine and compressor selected to provide such backpressure are poorly matched, and such a system results in less-than-optimal
15 performance, sacrificing fuel economy and power, especially at higher engine speeds.

In conjunction with the relatively small sized turbine discussed in the aforementioned paragraph, it is further known to provide a wastegate for
20 bypassing excess amounts of exhaust backpressure in an attempt to thereby increase engine power at relatively high speeds. The wastegate bypass

typically includes a modulating valve which modulates exhaust flow therethrough at a frequency synchronous with exhaust pulses. Although engine efficiency and power are improved overall, this solution still results in a smaller turbine being selected for the engine than is desired for optimal performance and fuel economy. Furthermore, the modulating valve of the wastegate bypass has been known to experience reliability problems due to the harsh engine environment in which it operates. In particular, the modulating valve of the wastegate bypass typically operates in close proximity to the engine's combustion chambers where exhaust temperatures, gas pressures and engine vibrations are greater. These factors decrease control over the wastegate valve which in turn decreases control over EGR flow and the engine in general.

In an attempt to overcome the problems of wastegated turbines having a small, fixed swallowing capacity, it is known to provide a variable geometry turbine with movable vanes that can be adjusted to vary the swallowing capacity and flow resistance of the turbine. However, this solution is only viable in situations where cost is not prohibitive, because variable geometry turbines are typically more expensive than wastegated turbines. Moreover, in these systems the boost and rotor speed provided by the turbine become dependent upon swallowing capacity of the turbine which results in less than desirable engine performance at various engine operating conditions.

Given that emissions regulations are increasingly becoming more stringent, an improved EGR system is needed.

- 5 An object of the present invention is to provide an improved exhaust gas recirculation (EGR) system for an internal combustion engine. Another object of the present invention is to provide an effective EGR system which is reasonably inexpensive. The present invention achieves these objects and overcomes deficiencies in the prior art by providing, in an embodiment, an
- 10 EGR system that utilizes a valve located downstream of an exhaust turbine. In an embodiment, the EGR system has a controller for controlling the valve to optimize engine performance and emissions depending upon the operating conditions.
- 15 The present invention is generally directed to an EGR system for a turbocharged internal combustion engine. The engine includes a turbocharger having a compressor for compressing air delivered to an intake manifold and an exhaust turbine arranged in an exhaust duct for driving the compressor. The EGR system includes an EGR duct extending between the intake duct and
- 20 exhaust duct to permit fluid communication therebetween. The EGR duct generally guides an EGR flow of exhaust gas from the exhaust duct to the

intake duct to achieve a reduction in nitric oxide emissions from the engine. A throttle valve is arranged in the exhaust duct downstream of an inlet port which opens to the EGR duct. The throttle valve is controlled by a controller for selectively restricting the flow through the exhaust duct, and thereby varying
5 backpressure upstream of the throttle valve, to adjust an amount of EGR flow through the EGR duct.

According to an embodiment of the present invention, a wastegate valve is arranged in parallel with the exhaust turbine and upstream of the throttle valve
10 to bypass a portion of the exhaust gas flow around the turbine. According to this embodiment, the exhaust turbine may be of the fixed geometry type with a fixed swallowing capacity.

According to another embodiment, the exhaust turbine is of the variable
15 geometry type. The variable geometry turbine includes variable geometry vanes controlling the swallowing capacity of the turbine and the turbine efficiency. An actuator, which is controlled by the controller, selectively adjusts the position of the variable geometry vanes to control the swallowing capacity of the turbine.

20

In an embodiment, the controller can at least partially close the throttle valve

during starting conditions. This results in creating higher backpressure and the burning of fuel at a higher rate to achieve idle conditions. This results in a higher rate of heat transfer into the engine components. In such a manner, the EGR system of the invention can advantageously decrease the time needed to
5 warm the engine.

In an embodiment, the controller can at least partially close the throttle valve during higher speed operation. This builds backpressure to provide compression resistance in the cylinders. Advantageously, the EGR system of
10 the invention can be controlled in such a manner to provide a compression braking.

It is therefore an advantage of a preferred embodiment of the present invention to provide an improved way to selectively increase or control the EGR flow in
15 a turbocharged internal combustion engine.

For turbocharged internal combustion engines that include a variable geometry turbine, it is a further advantage of a preferred embodiment of the present invention to decouple the swallowing capacity of the turbine from the boost
20 and rotor speed of the turbine.

For turbocharged internal combustion engines that include a wastegated turbine,
another advantage of a preferred embodiment of the present invention is to
provide a turbine that has an increased swallowing capacity to provide for
increased engine efficiency and power while maintaining the desired EGR flow
5 under certain engine conditions.

A further advantage of a preferred embodiment of the present invention is to
provide an enhanced EGR system which has few parts and a reasonable cost.

10 These and other features and advantages of the invention are disclosed in, and
will become apparent from, the detailed description of the presently preferred
embodiments and from the drawings.

FIG. 1 is a schematic illustration of an exhaust gas recirculation system for an
15 internal combustion engine in accordance with a first embodiment of the
present invention.

FIG. 2 is a schematic illustration of an exhaust gas recirculation system for an
internal combustion engine in accordance with a second embodiment of the
20 present invention.

FIG. 3 is a schematic illustration of an exhaust gas recirculation system for an internal combustion engine in accordance with a third embodiment of the invention.

5 Now referring to the drawings, wherein like numerals designate like parts, FIGS. 1 and 2 schematically an internal combustion engine 10 equipped with an EGR system 12, 14, respectively, providing exhaust gas recirculation. In each of these embodiments, the engine 10 includes an intake duct 16 having an intake manifold 18 delivering a flow of intake air to the engine cylinders 20
10 and an exhaust duct 22 having an exhaust manifold 24 carrying a flow of exhaust gas away from the cylinders 20 and ultimately to discharge into the ambient air, as indicated. In general, the EGR system 14 carries an EGR flow from the exhaust duct 22 back to the intake duct 16.

15 The engine 10 includes a turbocharger 26, 26', as illustrated in FIGS. 1 and 2, respectively, for compressing the intake air in a conventional manner. The turbocharger 26, 26' includes an exhaust turbine 28, 28', respectively, arranged in the exhaust duct 22 that is driven by the exhaust flow therethrough. The exhaust turbine 28, 28' is drivingly connected to an intake compressor 30 via a
20 common shaft 32 or other connection. The intake compressor 30 is arranged in the intake duct 16 to compress the intake air. A heat exchanger or intercooler

34 may also be arranged in the intake duct 16 downstream of the intake compressor 30 for cooling and increasing the density of the compressed intake air.

- 5 To facilitate the EGR flow, the EGR system 12, 14 includes an EGR duct 40 having an inlet port 42 connected to the exhaust duct 22 upstream of the exhaust turbine 28, 28' and an outlet port 44 connected to the intake duct 16, preferably downstream of the intake compressor 30 and intercooler 34. As the exhaust gas flows through the EGR duct 40, it preferably passes through an
- 10 EGR cooler 46 to lower its temperature to around 250 to 300 degrees F, to thereby increase the density of the exhaust gases in the EGR flow to effect a more efficient reduction in nitric oxide emissions.

- To selectively permit or restrict EGR flow, an embodiment of the EGR system
- 15 12, 14 includes an EGR valve 48 arranged in the EGR duct 40, preferably upstream of the EGR cooler 46. The EGR valve 48 may be a shutoff type valve which is selectively positioned in an open or closed position to selectively allow or shut off EGR flow. Alternatively, the EGR valve 48 can be operable in a modulating manner to selectively allow or restrict EGR flow.
- 20 Under certain operating conditions where EGR flow is unnecessary or could potentially create adverse effects to the engine, a controller 50 delivers a signal

via line 52 which actuates the EGR valve 48 to restrict or turn off the EGR flow. For example, the EGR valve 48 may be actuated to close during high transient torque demand situations, thereby shutting off flow through the EGR duct 40.

5

For selectively controlling exhaust backpressure and thereby controlling the EGR flow, the EGR system 12, 14 includes a throttle valve 54, as illustrated in FIGS. 1 and 2, respectively. In accordance with an embodiment of the present invention, the throttle valve 54 is located in the exhaust duct 22 downstream of the EGR inlet port 42. In general, the throttle valve 54 is operable to selectively restrict exhaust flow through the exhaust duct 22, thereby increasing backpressure upstream of the throttle valve 54 and, in turn, increasing the pressure differential across between the exhaust duct 22 and intake duct 16 across the EGR duct 40. By using the throttle valve 54 to control backpressure in this manner, the EGR flow can be controlled.

In a preferred embodiment, the throttle valve 54 is located downstream of the exhaust turbine 28, 28' where the valve 54 is subjected to less severe engine vibrations, gas pressures and thermal loads. This advantageously allows the use of a less expensive throttle valve 54 with lower tolerance requirements than required for an embodiment wherein the throttle valve 54 is located upstream

20

of the turbine 28. Locating the throttle valve 54 downstream of the exhaust turbine 28, 28' also generally increases the life span of the throttle valve 54 and therefore the reliability of the engine 10, 12. However, in another embodiment of the invention, the throttle valve 54 can be located upstream of the turbine
5 28, 28'.

To increase the EGR flow, the controller 50 sends a signal via line 56 to the throttle valve 54 to selectively control the degree of opening of the throttle valve 54 which thereby provides a selected flow restriction in the exhaust duct
10 22 downstream of the EGR inlet port 42. The restriction provided by the throttle valve 54 increases the back pressure in the exhaust duct 22 upstream of the throttle valve 54 which increases the portion of the exhaust flow introduced into the EGR duct 40, thereby increasing the EGR flow. The greater EGR flow achieves a more environmentally friendly engine by effecting increased
15 overall reductions in nitric oxide emissions. To decrease EGR flow, the controller 50 sends another signal via line 56 to the throttle valve 54 to provide a less restrictive restriction and thereby decrease the back pressure in the exhaust duct 22 and the amount of EGR flow. Decreasing EGR flow typically improves engine power, efficiency and performance.

20

In an embodiment, the controller 50 is capable of positioning the throttle valve

54 in an open position, a closed position, and variable positions therebetween.

The controller 50 selectively positions the throttle valve 54 in response to one or more sensed parameters, such as engine load, engine speed, EGR flow rate or another parameter as delivered by a signal to the controller 50 via one or
5 more input line 57. For example, at lower speeds, such as at low speed and high or partial loads, the controller may partially close the throttle valve 54 to provide a relatively high restriction to increase back pressure at the EGR inlet port 42 and thereby increase the EGR flow. At higher engine speeds, for example, the controller 50 causes the throttle valve 54 to open, thereby
10 decreasing the amount of flow restriction. The controller 50 is designed to control the throttle valve 54 in a desirable manner which may depend, for example, upon the particular configuration of the engine 10, the desired amount of nitric oxide emissions, the desired performance and output requirements of the engine 10, etc. In an embodiment, the throttle valve 54 is modulated, the
15 position typically being updated at a relatively low frequency corresponding to transitions between engine speed and load on the order of every couple of seconds.

In addition to increasing EGR flow, the throttle valve 54 is useful for
20 decreasing the warm up time for the engine 10 during initial engine starting.

For example, during engine startup, the throttle valve 54 may be fully or

substantially closed by the controller 50 to provide upstream back pressure in the exhaust duct 22. As a result, the engine 10 requires more fuel burn in order to achieve idle conditions. The higher fuel rate gives higher heat rejection to the engine coolant and, in turn, causes the engine 10 to warm up faster. Moreover, since EGR flow is usually avoided by closing the EGR valve 48 until the engine is warm, this reduces the time spent in a non-EGR/high nitric oxide (NO_x) emissions mode. By thus achieving a condition of EGR flow sooner, overall nitric oxide emissions are advantageously reduced.

10 The throttle valve 54 may also be additionally used for compression braking. According to this feature, the throttle valve 54 may be fully or substantially closed by the controller 50 to provide for high compression in the engine's cylinders 20. This may be used for compression braking to slow the speed of engine 10.

15

In the EGR system 12 illustrated in FIG. 1, the exhaust turbine 28 is a variable geometry turbine. The variable geometry turbine 28 includes variable geometry vanes which can be adjusted by an actuator 62 to control the swallowing capacity of the turbine 28. The variable geometry vanes also control the turbine efficiency. The actuator 62 may be controlled by the controller 50 via line 58. By combining the variable geometry turbine 28 with the throttle valve

54, the swallowing capacity (which can be controlled by either the variable geometry vanes or the throttle valve 54) can be controlled independently of the boost and rotor speed of the turbine 28 (which depends in part upon the position of the variable geometry vanes). It is an advantage that this provides for greater engine power, and improves specific fuel consumption and controllability. In the EGR system 12 of FIG. 1, the throttle valve 54 may also be partially closed by the controller 50 at higher engine speeds to increase back pressure and provide for increased EGR flow.

10 In the embodiments illustrated in FIGS. 2 and 3, the EGR system 14 includes an exhaust turbine 28' which can be a fixed geometry turbine. The exhaust duct 22 includes a wastegate duct 66 arranged in fluid parallel with the turbine 28' for bypassing excess pressure build-up in the exhaust duct 22 upstream of the turbine 28'. More specifically, the wastegate duct 66 is connected in fluid communication with the exhaust duct 22 at an inlet port located upstream of the turbine 28'. The wastegate duct 66 is connected to return flow to the exhaust duct at a reentry point downstream of the turbine 28'. The reentry point of wastegate duct 66 into exhaust duct 22 is located upstream of the throttle valve 54 in the embodiment of FIG. 2. However, as illustrated in FIG. 3, the reentry point of wastegate duct 66 into exhaust duct 22 can be located downstream of the throttle valve 54 in another embodiment of the invention.

As also illustrated in FIGS. 2 and 3, a wastegate valve 68 is located in the wastegate duct 66. The wastegate valve 68 is operable to restrict or modulate flow through the wastegate duct 66 to control rotor speed and efficiency of the turbine 28'. In this manner, the condition of the wastegate valve 68 can be controlled in order to regulate performance of the engine 12. The wastegate duct 66 and the wastegate valve 68 are effective to vary the swallowing capacity of the turbine 28'. The wastegate valve 68 is controlled by the controller 50 via line 70.

10 The embodiment including the throttle valve 54 in combination with fixed geometry turbine 28' and wastegate duct 66 provides several advantages. One advantage is that EGR flow rate can be increased by providing a selective flow restriction by selectively closing the throttle valve 54 at part load and also at low speed/high load, thereby achieving the desired reduction rate in nitric oxide

15 emissions to more easily comply with stringent emissions regulations. By increasing EGR flow rate, the injection timing may be advanced and fuel consumption improved. Because the throttle valve 54 may be used to build back pressure in the exhaust duct 22, the swallowing capacity of the exhaust turbine is not as critical for facilitating EGR flow, and therefore a larger

20 turbine 64 can be selected if desired to provide a better matched turbocharger 26 and therefore a more efficient, better performing engine 12, particularly at

higher engine speeds. Boost power may also be lowered with this embodiment to increase engine power. The throttle valve 54 may also be used for active compensation for variations in stack restrictions from one installation to another or changes in stack restriction over time. The throttle valve 54 may also be
5 used for active compensation for variations between engines or for engine degradation over time.

In the EGR system 14, the wastegate bypass 66 may discharge the wastegated exhaust flow either upstream as shown in FIG. 2, or downstream of the throttle
10 valve 54 as shown in FIG. 3. The throttle valve 54 may also be arranged to act on all exhaust flow to the exhaust stacks as illustrated, or alternatively any portion of the exhaust flow to the exhaust stacks regardless of whether the throttle valve 54 is located upstream or downstream of the exhaust turbine 28'.

15 All of the references cited herein, including patents, patent applications and publications are hereby incorporated in their entireties by reference. While this invention has been described in connection with exemplary embodiments, various changes and modifications will be apparent to those of ordinary skill in the art. Such changes and modifications may be made without departing from
20 within the spirit and the scope of the invention. Accordingly, the appended claims are intended to cover such changes and modifications.

CLAIMS

1. An internal combustion engine having an intake duct, an exhaust duct,
and an exhaust gas recirculation system comprising:
 - 5 an EGR duct connected in fluid communication with the exhaust duct for
guiding an EGR flow of exhaust gas from the exhaust duct to the intake duct;
an EGR cooler located in the EGR duct for cooling the EGR flow prior to
entering the intake duct;
an exhaust turbine in the exhaust duct downstream of said EGR duct,
10 the turbine driving an intake compressor ;
a throttle valve arranged in the exhaust duct downstream of said EGR
duct operable to selectably restrict flow through the exhaust duct; and
a controller operable to adjust the throttle valve.
- 15 2. An engine according to claim 1, wherein the throttle valve is located
downstream of the exhaust turbine.
3. An engine according to claim 1, wherein the controller adjusts the
throttle valve to vary back pressure in the exhaust duct to control a rate of said
20 EGR flow.

4. An engine according to claim 3, wherein the controller modulates the throttle valve as a function of engine speed.
5. An engine according to claim 3, wherein the controller substantially closes the throttle valve during a starting operation of the engine.
6. An engine according to claim 1, further comprising:
a wastegate duct in communication with the exhaust duct for bypassing a wastegate flow from the exhaust duct upstream of the exhaust turbine to reenter the exhaust duct downstream of the turbine; and
a wastegate valve located in the wastegate bypass duct for selectively restricting said wastegate flow.
7. An engine according to claim 6, wherein the turbine is of a type having fixed geometry vanes.
8. An engine according to claim 1, wherein the turbine includes variable geometry vanes and an actuator for selectively adjusting the position of the variable geometry vanes, the actuator being controlled by the controller.
9. An engine according to claim 1, wherein the controller is operable to

substantially close the throttle valve to cause back pressure in the exhaust duct for providing compression braking.

10. An engine according to claim 1, further comprising an EGR valve
5 located in the EGR duct adjustable to vary the EGR flow.

11. An engine according to claim 1, further comprising an intercooler located in the intake duct located upstream of the EGR duct.

10 12. An exhaust gas recirculation system for an internal combustion engine having an intake duct, an exhaust duct, and a turbocharger with a turbine located in the exhaust duct, the turbocharger driving a compressor located in the intake for charging air in the intake duct, the exhaust gas recirculation system comprising:

15 an EGR duct connected in fluid communication with the exhaust duct upstream of the turbine for guiding an EGR flow of exhaust gas from the exhaust duct to the intake duct;

an EGR cooler located in the EGR duct for cooling the EGR flow prior to entering the intake duct;

20 a throttle valve arranged in the exhaust duct downstream of said EGR duct operable to selectably restrict flow through the exhaust duct; and

a controller operable to adjust the throttle valve for controlling back pressure in the exhaust duct.

13. An exhaust gas recirculation system according to claim 12, wherein the
5 throttle valve is located downstream of the exhaust turbine.

14. An exhaust gas recirculation system according to claim 12, wherein the controller adjusts the throttle valve to increase back pressure in the exhaust duct for controlling a rate of said EGR flow.

10

15. An exhaust gas recirculation system according to claim 14, wherein the controller modulates the throttle valve as a function of one or more engine operating parameters.

15 16. An exhaust gas recirculation system according to Claim 15, wherein one of said engine operating parameters is engine speed.

17. An exhaust gas recirculation system according to Claim 15, wherein one of said engine operating parameters is engine load.

20

18. An exhaust gas recirculation system according to claim 14, wherein the

controller is operable to substantially close the throttle valve during a starting operation of the engine.

19. An exhaust gas recirculation system according to claim 12, further
5 comprising:

a wastegate duct in communication with the exhaust duct for bypassing a wastegate flow from the exhaust duct upstream of the exhaust turbine to reenter the exhaust duct downstream of the turbine; and

a wastegate valve located in the wastegate bypass duct for selectively
10 restricting said wastegate flow.

20. An exhaust gas recirculation system according to claim 19, wherein the turbine is of a fixed geometry turbine.

15 21. An exhaust gas recirculation system according to claim 19, wherein said controller is operable to adjust the wastegate valve.

22. An exhaust gas recirculation system according to claim 12, wherein the turbine includes variable geometry vanes and an actuator for selectively
20 adjusting the position of the variable geometry vanes, the actuator being controlled by the controller.

23. An exhaust gas recirculation system according to claim 12, wherein the controller is operable to substantially close the throttle valve to cause back pressure in the exhaust duct for providing compression braking.
- 5 24. An exhaust gas recirculation system according to claim 1, further comprising an EGR valve located in the EGR duct adjustable to vary the EGR flow.
25. A method of operating an internal combustion engine having an intake
10 duct, an exhaust duct, and a turbocharger having a turbine located in the exhaust duct driving a compressor located in the intake duct for charging intake air, and an EGR duct connected to guide an EGR flow from the exhaust duct to the intake duct, the EGR duct being connected in communication with the exhaust duct upstream of the turbine, the method comprising the steps of:
15 restricting flow through the exhaust duct at a location downstream of the EGR duct to adjust backpressure in the exhaust duct; and
cooling the EGR flow prior to entry into the intake duct.
26. A method according to claim 25, wherein said cooling step includes
20 providing an EGR heat exchanger located in the EGR duct.

27. A method according to claim 25, wherein said restricting step includes providing a throttle valve in exhaust duct downstream of said EGR duct.

28. A method according to claim 27, wherein said restricting step includes:
5 controlling the throttle valve in response to one or more engine operating parameters.

29. A method according to claim 28, wherein said controlling includes adjusting said throttle valve to control EGR flow.

10

30. A method according to claim 28, wherein said controlling includes substantially closing said throttle valve for a period after the engine is started to aid in warming up the engine.

15 31. A method according to claim 28, wherein said controlling includes adjusting said throttle valve to increase back pressure in said exhaust duct to effect compression braking of the engine.

32. An internal combustion engine substantially as described hereinbefore
20 with reference to the accompanying drawings and as shown in Figure 1, or in Figure 2 or in Figure 3 of those drawings.

33. An exhaust gas recirculation system substantially as described hereinbefore with reference to the accompanying drawings and as shown in Figure 1, or in Figure 2 or in Figure 3 of those drawings.

5 34. A method of operating an internal combustion engine substantially as described hereinbefore with reference to the accompany drawings.



INVESTOR IN PEOPLE

Application No: GB 0020230.9
Claims searched: 1 to 34

Examiner: John Twin
Date of search: 17 November 2000

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:
UK Cl (Ed.R): F1B (BB140)
Int Cl (Ed.7): F02D 9/04, 21/08; F02M 25/07
Other: online: EPODOC, JAPIO, WPI, TXTEP, TXTGB, TXTUS, TXTWO, MOBILITY

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
Y	EP 869275 A1 (Caterpillar) - note EGR cooler 38	1,12,25
Y	EP 622533 A1 (Volvo Penta) - note EGR cooler 19	1,12,25
Y	JP 11-082070 A (Toyota) - see WPI abstract accession no.1999-268676; Patent Abstracts of Japan, vol.199908 - note exhaust throttle 14	1,12,25
Y	US 5771867 (Caterpillar) - note exhaust throttle 56	1,12,25

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.